

DIRECTIONS FOR USE

RESTRAINTS

NOT TO BE USED on surfaces which come into direct contact with foodstuffs.

NOT TO BE USED on roofs for collections of potable water.

NOT TO BE USED on surfaces which come into direct contact with the ground.

Surfaces exposed to weather / rain are recommended to be sealed after application of BORACOL 200RH with a water repellent, paint or other suitable sealant.

APPLICATION TABLE

BORACOL 200RH can be applied by brush, roller, dipping or spraying.

Preventative Treatment	10 mL of BORACOL 200RH per 1000 cubic cm
Remedial / Insecticide Treatment	20 mL of BORACOL 200RH per 1000 cubic cm

SITUATION	STATES	RECOMMENDED RATE PER SQUARE METRE		
PREVENTION Timber, masonry brickwork, concrete	ALL STATES	0-25mm depth	25-50mm depth	50-100mm depth
		250 mL	500 mL	1 L

SITUATION	STATES	RECOMMENDED RATE PER SQUARE METRE		
REMEDIAL/ INSECTICIDE Timber, masonry brickwork, concrete	ALL STATES	0-25mm depth	25-50mm depth	50-100mm depth
		500 mL	1 L	2 L

NOT TO BE USED FOR ANY PURPOSE OR IN ANY MANNER CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

CAUTION

KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING



ACTIVE CONSTITUENTS:

52 g/L BORON (B) present as DISODIUM OCTABORATE TETRAHYDRATE
12 g/L BENZALKONIUM CHLORIDE SOLVENT: 886g/L MONOETHYLENE GLYCOL

FOR INDUSTRIAL/DOMESTIC USE IN PRE-TREATMENT AND REMEDIAL TREATMENT OF TIMBER AGAINST DECAY AND INSECTS.
ALSO FOR THE TREATMENT OF OTHER SURFACES THAT HAVE BEEN IN CONTACT WITH AFFECTED TIMBER.

NET CONTENTS:

Manufactured in Australia by:

Osmose

PO Box 499 Mount Gambier
South Australia 5290 AUSTRALIA
Phone: 1800 088 809

An **Osmose** Quality Product

GENERAL INSTRUCTIONS

BORACOL 200RH is effective in controlling surface mould, algae and fungi. It will also at the insecticide rate help control common wood borers and termites.

BORACOL 200RH is supplied ready for use for in-situ, remedial preventative treatment as per application table.

If the surface to be treated is very dry the penetration of BORACOL 200RH will be enhanced if the surface is sprayed with water prior to treatment. This is always necessary when using the remedial / insecticide rate for the treatment of aged timbers with very dry surfaces. BORACOL 200RH can be applied immediately after the water has been absorbed by the surface.

When using high rates (remedial / insecticide) it may be necessary to apply via two coatings with two to three hours interval.

PROTECTION OF WILDLIFE, FISH, CRUSTACEA AND ENVIRONMENT

Do not contaminate streams, rivers or waterways with the chemical or used containers.

STORAGE AND DISPOSAL

Store in original closed container in a dry, cool, well ventilated area. Do not store for long periods in direct sunlight. DO NOT use the container for any other purpose. Triple or preferably pressure rinse containers before disposal. Dispose of rinsings in a disposal pit specifically marked and set up for this purpose, clear of waterways, desirable vegetation and tree roots.

(For All Pack Sizes except 1000L)

Break, crush or puncture and bury empty containers in a local authority landfill. If no landfill is available, bury the containers below 500mm in a disposal pit. Empty containers and product should not be burnt.

(For 1000L Packsize)

Empty contents fully into application equipment. Close all valves and return to point of supply for refill or storage.

SAFETY DIRECTIONS

Will irritate the eyes, nose and throat and skin. Avoid contact with eyes and skin. Do not inhale spray mist. After use and before eating, drinking or smoking, wash hands, arms and face thoroughly with soap and water.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre.

Phone Australia 13 11 26. If swallowed, and if more than 15 minutes from a hospital, induce vomiting preferable using Ipecac Syrup APF.

CONDITIONS OF SALE

Osmose Australia Ltd. ("Osmose") shall not be liable for any loss, injury, damage or death whether consequential or otherwise whatsoever or howsoever arising whether through negligence or otherwise in connection with the sale, supply, use or application of this product. The supply of this product is on the express condition that the purchaser does not rely on Osmose skill or judgment in purchasing or using the same and every person dealing with this product does so at their own risk absolutely. No representative of Osmose has any authority to add or alter these conditions.

Additional information is listed in the Material Safety Data Sheet

BATCH NUMBER

Date of Manufacture

NRA APPROVAL NUMBER 30711 / 0899

IN CASE OF EMERGENCY PHONE 1800 039 008