

Directions for Use:

Termatrix Termite Bait must be used only as part of an integrated termite management program by termite specialists approved by Sherwood Chemicals Australasia Pty Ltd.

Situation	Pest	Rate	Critical Comments
For use in Integrated Termite Management Programs in and around residential and commercial properties, including food handling establishments and other areas where termite presence can be detected, e.g. fences, utility poles, trees, bridges, wharves and landscape structures in all areas of Australia except Tasmania.	Subterranean termites (except <i>Mastotermes darwiniensis</i>)	Mix 100 g of bait matrix with 300-400 mL of clean water. Up to 100 mL additional water may be added if conditions are hot and dry.	Do not use water that has been chlorinated or contaminated in any way. Stir until paste of uniform consistency is achieved. Add bait as necessary to approved bait stations or directly into termite workings. Replenish as required. When handling the bait matrix wear disposable latex rubber gloves to ensure odours or contaminants that may deter termite feeding are not transferred to the bait matrix. Note: 300 mL of bait matrix equals 100 g

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

GENERAL INSTRUCTIONS

Termatrix is used with in-ground and above-ground Stations and can contain up to 400 g of bait paste. Termatrix in-ground stations are designed to intercept foraging termites with timber interceptors and to concentrate their feeding in the stations. In-ground stations containing timber interceptors are embedded in the soil around the perimeter of the building at intervals of 3 - 5 metres. Station placement is focused in areas where termites are most likely to be found foraging. These stations are inspected on a regular basis at approximately 8 to 12 week intervals until termites are intercepted. (Inspections are more frequent during the warmer summer months and first inspection sooner if the building is under termite attack at the time of initial station installation.) At this point, Intra-bait is added to the Station. Baited Stations should be inspected every 3 - 8 weeks with the more frequent inspections

occurring during the initial stages of termite feeding. When the colony has been eliminated, the termatrix is removed and fresh timber interceptors are placed in the stations. These stations should continue to be monitored on a regular basis. Where live termites are feeding within a building, above-ground stations containing termatrix are installed on areas of termite feeding. These are removed once the colony has been eliminated, or if no feeding occurs. Bait may also be placed directly into termite workings. Termatrix above-ground stations should be inspected at least 3 - 6 weekly with the more frequent inspections occurring during the initial stages of termite feeding. Bait is replenished or moistened slightly with clean water to maintain its attractiveness in feeding stations.

Termatrix

Termite Bait

ACTIVE CONSTITUENT: 1.0g/kg CHLORFLUAZURON

An insect development inhibitor type insecticide for use as part of a termite interception and baiting system, an integrated system for the management of subterranean termite infestations (except *Mastotermes darwiniensis*).



Sherwood Chemicals Australasia Pty Ltd
Level 3, 1060 Hay Street
WEST PERTH 6005
AUSTRALIA
ABN: 351 369 936 30
Tel: +61 89219 4683 Fax: +61 89219 4672
Web: www.sherwoodchemicals.com.au

NET CONTENTS 500 g
APVMA Approval No: 64650/500g/0610

NET CONTENTS 2 kg
APVMA Approval No: 64650/2kg/0610

NET CONTENTS 3 kg
APVMA Approval No: 64650/3kg/0610

NET CONTENTS 4 kg
APVMA Approval No: 64650/4kg/0610

NET CONTENTS 8 kg
APVMA Approval No: 64650/4kg/0610

Termite Management

To minimize the risk of termite infestation, the subfloor area of buildings should be kept free of any stored product that contains cellulose and any other building materials that attract termites. Appropriate actions should also be taken to eliminate any undue dampness caused by leaking water or sewerage pipes, or inadequate drainage.

Service Requirement

Regular, competent inspections by a licensed Pest Manager are recommended as part of an overall termite management program to determine the prevailing termite pressure and environmental conditions and consequent requirement for further termite management options. Inspections should be performed at least on an annual basis, but more frequent inspections are strongly recommended.

PROTECTION OF WILDLIFE, FISH, CRUSTACEANS AND ENVIRONMENT

Dangerous to aquatic arthropods.
DO NOT contaminate streams, rivers or waterways with the chemical or used containers.
DO NOT place Termatrix in any area where, because of movement of water, it could be washed into a body of water containing aquatic life, such as ponds or streams.

NOTICE

Sherwood Chemicals Australasia Pty Ltd warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with Directions for Use under normal conditions of use. No warranty of merchantability or fitness for a particular purpose, express or implied, extends to the product contrary to label instructions or under off-label permits not endorsed by Sherwood Chemicals Australasia Pty or under abnormal conditions.

STORAGE AND DISPOSAL

Store in the closed, original container in a dry, cool, well ventilated area out of direct sunlight. Single rinse before disposal. Dispose of rinsings in a disposal pit specifically marked and set up for this purpose, clear of waterways, desirable vegetation and tree roots. Puncture and bury empty containers and dispose of unused bait in a local authority landfill. If no landfill is available, bury the containers or unused bait below 500mm in a disposal pit. Empty containers and product should not be burnt.

SPILLS

Sweep up material and wrap in paper. Dispose of as above. Prevent entry of spilled matter into drains and waterways.

FIRST AID

If poisoning occurs, contact a Doctor or Poisons Information Centre.
Phone Australia 131126.

MATERIAL SAFETY DATA SHEET

Additional information is listed on the Material Safety Data Sheet which is available from Sherwood Chemicals Australasia Pty Ltd on request. Call Customer Service on 08 9219 4683 or visit our website at <http://sherwoodchemicals.com.au>

Batch Number:
Date of Manufacture: